



Maintenance Data Sheet Brass Stair Nosings

January 2015

1. Company Details

Manufacturer: C.A.T. Limited
Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire, LU3 3BP
United Kingdom
T: +44 (0)1582 561500 F: +44(0)1582 561900 E: sales@cat-accs.com

2. Product Composition

Brass alloy CW624N MN

3. Product maintenance:

Immediately after installation and removal of protective tape these profiles should be wiped over with a dry, soft cloth, to remove any handling marks and fingerprints.

Polished Finish: These brass profiles are produced with a highly polished finish. Regular cleaning with a suitable metal polish and soft cloth is advised to maintain their finish, making sure all traces of polish are removed during polishing. Alternatively trims can be left to age oxidize for a natural finish.

Satin Brass Finish: Wipe with a dry cloth or duster. Do not use any liquids on these finishes. To remove scuffs and small scratches a green Scotch pad can be used, rubbed along the grain of the existing finish.

Antique Finishes: Wipe with a dry cloth or duster. Do not use any liquids on these finishes.

PVC inserts: Clean with a mild detergent diluted with water on a damp - not wet - cloth, ensuring that inserts are wiped dry before the staircase is open to traffic.

Polishes and industrial cleaning agents should not be used on treads and inserts and may prove hazardous if used.

Avoid contact with water and all forms of moisture. Prolonged contact with moisture or chemicals will accelerate the oxidation process and leave marks that are difficult to remove with normal cleaning methods.

Care must be taken to protect surrounding floor finishes during maintenance.